

Over 130 years of Experience.

PPC Insulators is a specialist in the field of high voltage porcelain solutions with more than 130 years of experience in designing and manufacturing solid core post insulators.

Now, PPC Insulators is able to respond quickly and comprehensively also to customer demands regarding Medium Voltage post insulators. PPC Medium Voltage procelain post insulators are solutions for reliable and prologned use with no measurable aging in all power system facilities.

Quality of PPC Porcelain MV insulators

Compliance with all globally requested quality standards and exceed international standards and norms to provide ample safety margins for its customers:

- IEC © Standards 60273
- ISO 9001
- ISO 14001

Porcelain solution for unlimited lifetime

Index



Page T	itle
2 INTRODUCTION	NC
3 INDI	EX
4 PPC EURO	PE
5 WHY CHOOSE PI	PC
6 PRODUCT & PACKING DETAIL	LS
7 BIL 60	kV
8 BIL 75	kV
9 BIL 95	kV
10 BIL 125	kV
12 BIL 150	kV
14 BIL 170	kV
16 BIL 200	kV
18 BIL 250	kV
20 BIL 325	kV



Porcelain Insulators from PPC are manufactured and tested under strict production and quality control, in full accordance with IEC 60273. All MV insulators are stocked and delivered from PPC Europe.

- Proximity to each market with a worldwide footprint guarantees the excellent availability of PPC's products
- A comprehensive local customer service guaranteed by our global sales organization and supported by highly qualified local PPC representatives that provide competent personal service to every single customer
- Quick responses to our customers' delivery requirements by combining modern tools for design and leveraging our multiple manufacturing sites and warehouses
- Tailored solutions serving customer specific design requirements by PPC's international engineering team





Why Choose PPC for Supply of MV Insulators?

PPC's experience, developed technology, and persistent quality stand behind its reputation of the long term and professional partner with a high level of reliability in its product and services.





Legacy & Expertise
Over 130 years of experience.



Fast response time to our customers's inquiries and delivery needs.




Partnership and striving for building mutually beneficial long term relations.



Understanding of customer needs and hig level of services. PPC MV porcelain post insulators are solutions for reliable and prolonged use with no measurable aging in all power system facilities.

PPC Insulators offers better services with short delivery time for IEC post insulators ≤ 325kV BIL.



Standard Product Details

BIL (kV)	Height H (mm)	Bending Strength Range (kN)	Pollution Class Range *	Creepage Distance up to (mm)	Top PCD Pitch Circle Diameter D2 (mm)	Bottom PCD Pitch Circle Diameter D3 (mm)
60	190	4 to 8	a to d	190	76 (4 x M12)	76 (4 x M12)
75	215	4 to 8	a to c	250	76 (4 x M12)	76 (4 x M12)
95	255	4 to 12,5	a to c	380	76 (4 x M12)	76 (4 x M12)
125	305	4 to 12,5	a to d	600	76 (4 x M12)	76 (4 x M12)
150	355	4 to 10	a to d	660	76 (4 x M12)	76 (4 x M12)
170	445	4 to 10	a to e	1 120	76 (4 x M12)	76 (4 x M12)
200	475	4 to 12,5	a to d	913	76 (4 x M12)	76 (4 x M12)
250	560	4 to 12,5	a to e	1 620	76 (4 x M12)	76 (4 x M12)
325	770	4 to 12,5	a to e	2 260	127 (4 x M16)	127 (4 x M16)

Standard Packing Details

C12,5 - 325 - 2260

PPC Catalogue No. IEC description **Quantity of Units per Pallet** C8 - 60 - 190 342 150 4D34 0814 48 C8 - 75 - 250 342 150 4D35 0814 32 C12,5 - 95 - 380 342 150 4D36 0814 40 C8 - 125 - 600 342 150 4D37 0814 32 C12,5 - 125 - 600 342 150 4D38 0814 C6 - 150 - 660 342 150 4D10 0814 40 C10 - 150 - 660 342 150 4D11 0814 40 C6 - 170 - 900 24 342 150 4D12 0814 C10 - 170 - 1120 342 150 4D13 0814 24 C8 - 200 - 913 342 150 4D14 0814 24 C12,5 - 200 - 913 342 150 4D15 0814 24 C6 - 250 - 1620 342 150 4D16 0814 24 C12,5 - 250 - 1620 342 150 4D17 0814 C12,5 - 325 - 1450 342 150 4D18 0814 12 12

342 150 4D19 0814

* Pollution Class Range:

a = 12.7 mm/kVb = 16,0mm/kV

c = 20,0 mm/kVd = 25,0 mm/kV

e = 31,0 mm/kV

